

(12) United States Patent

Chang et al.

(54) INTEGRATED TOUCH SCREENS

(71) Applicant: Apple Inc., Cupertino, CA (US)

Inventors: Shih Chang Chang, Cupertino, CA

(US); John Z. Zhong, Saratoga, CA

(US)

Assignee: Apple Inc., Cupertino, CA (US)

Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 188 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 14/838,234

(22)Filed: Aug. 27, 2015

(65)**Prior Publication Data**

> US 2015/0370378 A1 Dec. 24, 2015

Related U.S. Application Data

- Continuation of application No. 14/666,174, filed on Mar. 23, 2015, now Pat. No. 9,146,414, which is a (Continued)
- (51) Int. Cl. G06F 3/041 (2006.01)G06F 3/044 (2006.01)(Continued)
- (52)U.S. Cl. G06F 3/044 (2013.01); G02F 1/1368 CPC (2013.01); G02F 1/13306 (2013.01); (Continued)
- (58) Field of Classification Search CPC G06F 3/041 See application file for complete search history.

(45) Date of Patent:

(10) Patent No.:

*Aug. 8, 2017

US 9,727,193 B2

(56)References Cited

U.S. PATENT DOCUMENTS

6/1956 Kirkpatrick G01R 25/00 323/233 3,333,160 A * 7/1967 Gorski F16K 31/02 251/129.04

(Continued)

FOREIGN PATENT DOCUMENTS

ΑU 2005246219 12/2005 CA1243096 A 10/1988 (Continued)

OTHER PUBLICATIONS

Non-Final Office Action mailed Oct. 8, 2015, for U.S. Appl. No. 14/670,306, filed Mar. 26, 2015, four pages. (Continued)

Primary Examiner — Vijay Shankar Assistant Examiner — Cory Almeida (74) Attorney, Agent, or Firm — Morrison & Foerster LLP

(57)**ABSTRACT**

Integrated touch screens are provided including drive lines formed of grouped-together circuit elements of a thin film transistor layer and sense lines formed between a color filter layer and a material layer that modifies or generates light. The common electrodes (Vcom) in the TFT layer can be grouped together during a touch sensing operation to form drive lines. Sense lines can be formed on an underside of a color filter glass, and a liquid crystal region can be disposed between the color filter glass and the TFT layer. Placing the sense lines on the underside of the color filter glass, i.e., within the display pixel cell, can provide a benefit of allowing the color filter glass to be thinned after the pixel cells have been assembled, for example.

21 Claims, 16 Drawing Sheets

